

Installation Instructions (Use with Copper, CPVC, SST & *PEX).

*Some PEX products may require tube inserts to maintain size or roundness.



Cut PEX, Copper, CPVC or SST tubing clean and square, removing burrs or sharp edges. Tubing should be round and free of score marks.



Push the tubing into the fitting until it reaches the tubing stop.

Note: You may mark the depth on the tubing using a gauge.



With the system depressurized, loosen the retaining cap using the wrench and turn counter clockwise until the retaining cap is removed from the fitting.



Insert the removal clip by opening the clip and sliding it over the tubing with the sloped edge facing the inside of the fitting.



With the removal clip installed, hand tighten the retaining cap into the fitting.



Grip the fitting and the tube, pull the tubing from the fitting to remove. Once the fitting is released, remove the removal clip, then reassemble for reuse.

Installation Caution!



-  **Insert only Copper, PEX, CPVC or Stainless Steel tubing into the valves. Do not insert fingers or body parts into the quick connection or grip rings. Immediate emergency medical attention or surgical care may be required for removal.**
-  **Heat or glues should never be applied in the installation of our quick connection valves. Do not solder within 10" of the valve.**
-  **Tube ends should be clean, round, free from damage, with smooth clean cuts. Jagged or sharp edges must be removed prior to insertion into the valve.**
-  **When using PEX tubing, some PEX tubing sizes may vary by manufacturer, which may require the use of a tubing insert for proper installation.**
-  **Water and heating systems must be free from contaminants chemicals, aggressive metals and have a balanced PH level.**

25 Year Copro™ Warranty

Quick Fitting Inc., hereafter referred to as "Quick Fitting", warrants its COPRO™ fittings and adapters to be free of defects in material and workmanship in water service and other approved materials, for a period of twenty-five (25) years from the date of purchase of the products.

Quick Fitting™ makes no other warranties, express or implied. This limitation explicitly excludes any implied warranty of merchantability or fitness for a particular purpose. The sole remedy for breach of this warranty of material and workmanship or for negligence in manufacture or design is limited to replacement or repair or the fitting, at the sole option of Quick Fitting, of any defective parts which are returned to Quick Fitting™ (prepaid) within twenty-five (25) years of original purchase. In no event shall Quick Fitting™ be liable for indirect, special, incidental or consequential damages of any kind. No allowance will be made for repairs made by the purchaser.

THIS WARRANTY IS EXPRESSLY IN LIEU OF ANY AND ALL OTHER WARRANTIES AND REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE AND THE WARRANTY OF MERCHANTABILITY. THERE ARE NO WARRANTIES, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. THE EXCLUSIVE REMEDY FOR DEFECTIVE PRODUCTS SHALL BE ONLY AS STATED HEREIN.

Quick Fitting™ does not warrant the design, assembly or installation of the system using COPRO, but only the components as stated herein. Quick Fitting is not responsible for improper design, assembly or installation, or for any modifications of the Quick Fitting™ products.

The warranty herein is void upon:

- failure to follow any of the assembly or installation guidelines,
- alteration, misuse or abuse of, or damage to, any of the Quick Fitting products,
- operation beyond the design range, excessive pressure or stress, or mishandling in any way,
- use other than for the intended purpose or in a manner other than as specified by Quick Fitting, or
- improper assembly, installation, service or maintenance.
- use on fluids that are aggressive, acidic, imbalanced PH or containing metals or chemicals.

This Limited Warranty, and Quick Fitting's responsibility, may be further limited, but may not be expanded, by Quick Fitting's terms and conditions of sale, as set forth on the reverse side of the Quick Fitting™ invoice.